



1/4"

**STANDARD**

Cable type : *5062*  
Reference : *EC1-50*

Cable with standard UV resistant PE jacket, halogen free according to IEC 60754

**FLAME RETARDANT**

Cable type : *5062-HLFR*  
Reference : *EC1-50-FR*

Cable with UV resistant, halogen free, low smoke flame retardant jacket according to IEC 60754, IEC 60332-1, IEC 60332-3 cat. C and IEC 61034

**CHARACTERISTICS**

**Construction**

- **Inner conductor**
  - Material **copper clad aluminium wire**
  - Diameter (mm) **2.4**
- **Dielectric**
  - Material **gas-injected cellular polyethylene**
  - Diameter (mm) **6.5**
- **Outer conductor**
  - Material **corrugated copper tube**
  - Diameter (mm) **7.5**
- **Outer sheath**
  - Material **black polyethylene**
  - Thickness (mm) **1.1**
  - Diameter (mm) **9.7**

**Mechanical characteristics**

- **Minimum bending radius**
  - a) single bending (cm) **3**
  - b) 15 repeated bends (cm) **8**
- **Maximum pulling strength (daN)** **40**
- **Recommended temperature range**
  - Storage **-70 to +85 °C**
  - Installation **-40 to +60 °C**
  - Operation **-55 to +85 °C**
- **Max. length per hoisting grip (m)** **70**
- **Maximum hanger spacing (m)** **-**
- **Flat plate crush resistance (kg/mm)** **0.8**
- **Bending moment (Nm)** **1.5**
- **Approximate weight<sup>[4]</sup> (kg/km)** **111 / 124**

**Electrical characteristics**

- Characteristic impedance ( $\Omega$ ) **50 ± 1**
- Nominal capacity (pF/m) **82**
- Relative propagation velocity (%) **82**
- Inductance ( $\mu$ H/m) **0.203**
- DC-resistance at 20°C
  - inner conductor ( $\Omega$ /km) **5.85**
  - outer conductor ( $\Omega$ /km) **3.3**
- RF peak voltage (kV) **0.8**
- RF peak power (kW) **6.9**
- Cut-off-frequency (GHz) **18.6**
- Insulation resistance (M $\Omega$ .km) **>> 5000**
- **Attenuation<sup>[1]</sup> and power rating**

Frequency (MHz)	Attenuation at 20°C <sup>[2]</sup> (dB/100m)	Mean power rating <sup>[3]</sup> (kW)
10	1.33	5.64
20	1.89	3.98
30	2.32	3.24
80	3.83	1.96
100	4.29	1.75
150	5.29	1.42
200	6.14	1.23
300	7.58	0.99
400	8.81	0.85
450	9.38	0.80
500	9.91	0.76
600	10.92	0.69
700	11.86	0.63
800	12.73	0.59
894	13.52	0.56
960	14.05	0.54
1000	14.36	0.52
1500	17.90	0.42
1700	19.18	0.39
1800	19.79	0.38
1880	20.27	0.37
2000	20.98	0.36
2170	21.95	0.34
2200	22.12	0.34
2300	22.68	0.33
2400	23.22	0.32
2500	23.76	0.32
2700	24.81	0.30
3000	26.33	0.29
4000	31.02	0.24
6000	39.25	0.19

[1] The attenuation can be approximated by the formula:

$$\alpha(f[\text{MHz}]) = A \cdot \sqrt{f[\text{MHz}]} + B \cdot f[\text{MHz}] \quad (\text{dB}/100\text{m})$$

A = 0.41769  
B = 0.00115

[2] Nominal values

[3] Ambient temperature = 40°C; temperature of inner conductor = 100°C; VSWR = 1.0; no solar loading

[4] Standard PE jacket / HLFR Jacket

